

---

## MX84 Datasheet

By Jonathan Roszkowski

**i** Note - The MX18.1 firmware release will be the maximum running build for MX64, MX64W, MX65, MX65W, MX84, MX100, and vMX100 platforms. These platforms will not run MX 18.2 and above firmware builds. We recommend you stay up to date with all the latest features with the next-generation hardware platforms. **Please consult your sales representative for more information on the latest hardware and software releases.** Thank you

---

## Overview

The Meraki MX84 is an enterprise security appliance designed for distributed deployments that require remote administration across Medium branch environments. It is ideal for network administrators who demand both ease of deployment and a state-of-the-art feature set. The Meraki Dashboard allows for simple and easy deployment of the MX84 with minimal pre-configuration in almost any location. Providing 2 dedicated WAN uplinks, 8 GbE RJ45 ports, and 2 SFP ports, the MX84 is ready for deployment in a variety of enterprise environments.



---

## Features

- Managed via the Cisco Meraki Dashboard
- Meraki AutoVPN and L2TP/IPSec VPN endpoint
- Automatic Firmware upgrades
- Active Directory integration
- WAN Link Balancing
- Content Filtering
- Automatic WAN Failover
- Malware Protection (AMP) w/ optional Threat Grid integration
- SD-WAN over Meraki AutoVPN
- IDS/IPS protection

- L3/L7 Stateful Firewall
- Geo-based firewall rules
- 1:1 and 1:Many NAT
- Configurable VLANs / DHCP support
- Static Routing
- Client VPN endpoint
- Custom Traffic Shaping
- Historical Client Usage statistics
- Netflow support
- Syslog integration
- Remote Packet Capture tools

## Hardware Features

- Dual Dedicated WAN uplinks
- A built-in USB port for failover cellular support
- 2 SFP ports

## Configuration

The basic initial configuration of the MX84 is just as simple as any other MX models. The links below provide additional information and instructions relating to each step in getting the device setup and configured for the first time.

1. [Claim the device to an Organization on the Meraki Dashboard](#)
  - a. If a Dashboard Organization does not yet exist, [Create one](#)
2. [Add the device to a Dashboard Network](#)
  - a. If a Network does not yet exist, [Create one first](#)
3. Physically connect the device to the local network
  - a. Ensure the wireless antennas are connected correctly (Wireless models only)
  - b. Power on the device and let it check in to the Dashboard
  - c. If necessary, configure a Static IP on the WAN interface through the [Local Status Page](#) to allow it to check in.
4. Finish configuring the device from the Meraki Dashboard
  - a. [Manage local VLANs](#)
  - b. [Modify Firewall rules](#)
  - c. [Configure VPN connectivity](#)

## Context and Comparisons

Description	MX65	MX84
Dual WAN Uplinks	Yes	Yes

Description	MX65	MX84
Backup Cellular Uplink	Via 3rd Party USB Modem	Via 3rd Party USB Modem
Stateful Firewall Throughput	250 Mbps	500 Mbps
Maximum VPN Throughput	100 Mbps	250 Mbps
Advanced Security Throughput	200 Mbps	320 Mbps
Maximum Concurrent VPN Tunnels	50	100
PoE Capabilities	Yes, 2x GbE RJ45 LAN Ports	-
Recommended LAN Clients	50	200

---

## Technical Breakdown

---

### Physical Interfaces

<b>WAN interface</b>	2x Dedicated GbE RJ45
<b>Cellular interface</b>	1x Cellular uplink via 3rd party USB Modem
<b>LAN Interface</b>	8x Dedicated GbE RJ45 ports, 2x Dedicated GbE SFP ports
<b>Management Interface</b>	1x Dedicated management port.

---

### Throughput and Capabilities

Description	MX84
<b>Recommended Maximum LAN Clients</b>	200
<b>Max Stateful Firewall Throughput in NAT mode</b>	500 Mbps
<b>Max VPN Throughput</b>	250 Mbps
<b>Max Concurrent VPN Tunnels (Site-to-Site or Client VPN)</b>	100

---

### Physical

Description	MX84
-------------	------

<b>Mount Type</b>	1U Rack
<b>Dimensions</b> (h x d x w)	1.75in x 10in x 19in (44mm x 254mm x 483mm)
<b>Weight</b>	9 lb (4.1kg)
<b>Power Supply</b>	Internal 100-220V
<b>Power Load (idle/max)</b>	26W / 32W
<b>Operating Temperature</b>	32°F - 104 °F 0°C - 40°C
<b>Humidity</b>	5% to 95%

---

## Accessories

Accessory	Description
MA-SFP-1GB-SX	Cisco Meraki 1 GbE SFP SX Fiber Module (1000BASE-SX, range: 550m)
MA-SFP-1GB-TX	Cisco Meraki 1 GbE RJ45 Copper Module (1000BASE-T for twisted pair)
MA-PWR-CORD-US	1x AC Power Cable, US plug
MA-PWR-CORD-EU	1x AC Power Cable, EU plug
MA-PWR-CORD-UK	1x AC Power Cable, UK plug
MA-PWR-CORD-AU	1x AC Power Cable, AU plug

---

## Warranty

MX Warranty coverage periods are as follows:

Product	Warranty Period	Warranty Information
MX84	Lifetime	Full lifetime hardware warranty with next-day advanced replacement included.
MX84 Accessories	1 Year	The following are considered accessories: SFP Modules, all mounting kits and stands, interface modules, additional power cords

Additional warranty information can be found on the [Return Policy and Requesting an RMA](#) page of the Cisco Meraki website.

If your Cisco Meraki device fails and the problem cannot be resolved by troubleshooting, contact support to address the issue. Once support determines that the device is in a failed state, they can process an RMA and send out a replacement device free of charge. In most circumstances, the RMA will include a pre-paid shipping label so the faulty equipment can be returned.



---

## Common Event Log Messages

There are currently no MX84 specific Event Log entries, for more general information about navigating the Event Log and the types of Events that could be expected please check out our [Event Log documentation](#).